

ECOVIP 310




TECHNICAL DATA

STANDARD

OPTION





STANDARD OUTFITTING PROVISIONS Towbar / Hidden wiring for cabinets - roof - power supply unit / Additional fresh water tank with level reading / Generator installation system / Reverse camera / Turbovent roof-light in the bathroom and the kitchen

(##) Before starting to drive, check that the level of the fresh water tank does not exceed 20 Lt.; (&) With furniture version "Noce Melinga" the table is in white laminate (instead of anthracite); (*) Optional window on right side of living room; (***) Optional window in washroom; (@@) With Fiat 43 mechanics (only with 3.800 and 4.035 mm connection) and 180 HP engine the maximum allowable mass is 4,400 Kg; (PTM) TIW stands for Total Increased Weight, or the potential expected increase in weight; (*) The right hand drive version is not available with 115 HP engines, but only with 130, 150 or 180 HP; (^^) The Fiat 43 mechanicsis only possible with engines 130, 150 or 180 HP; (°) Child-size bed included; (@) Should a motorcycle rack be installed or the Heavy chassis be downgraded, the number of type-approved seats may vary; (°°) With the drop-down bed, the Midi-Heki roof-light will be replaced by a Mini-Heki roof-light; (#) Weight in running order includes: 75 Kg for the driver, fuel and fresh water tanks (20 Lt) at 90% of capacity, gas at 90% and electric cable, basic standard version. Variance is possible within the tolerance levels of the materials and production processes used. The weights and type-approved seats vary according to engine size, model and accessories supplied.

| Engine displacement (cc) | ABS, EBD, ESP Traction+, Hill Holder, Hill Descent | • | |
|---|--|----------------|--------------------------------------|
| Engine displacement (cc) | Drive | 110110 | |
| Fuel tank Gearbox 5+1 | Engine | | |
| Gearbox 5+1 6+1 Maximum power kW (HP) 85 (115) 96 (130) 109 (150) 130 (180) Mechanics(*)(**)** Fiat Ducato 35 Fiat Ducato 43 Version Euro 5+ Wider rear track DIMENSIONS AND WEIGHTS ** DIMENSIONS AND WEIGHTS External length 6.590 mm ** External width 2,300 mm Internal height Internal height 2,100 mm Internal width Maximum total weight 3.650 - 4.250 - 4.400Kg(PTM) Overall height 2,920 mm Payload (about) 696 Kg 846 - 1.406 - 1.556 Kg(PTM) Towable mass 1,600 Kg 2,000 Kg (130 150 180 HP) Type-approved seats(@) 4 5 Weight in running order(#) 2,804 Kg 2,804-2,844-2,844 Kg(PTM Wheelbase 3.800 mm THICKNESS Floor 55 mm Roof Roof 40 mm 35 mm TANKS Additional fresh water tank 80 l. Fresh water tank (heated and anti-freeze)(##) 80 + 20 l. Was | Engine displacement (cc) | 2,000 | 2,300 - 3,000 |
| Maximum power kW (HP) 85 (115) 96 (130) 109 (150) 130 (180) Mechanics(^)(^^) Fiat Ducato 35 Fiat Ducato 43 Version Euro 5+ Wider rear track DIMENSIONS AND WEIGHTS External length External width Internal width 2,300 mm Internal width 217 cm Maximum total weight Overall height 2,920 mm Payload (about) Towable mass 1,600 Kg 1,600 Kg 2,000 Kg (130 150 180 HP) (PTM) Type-approved seats(@) Weight in running order(#) Wheelbase 3,800 mm THICKNESS Floor Floor Floor Floor Floor Walls TANKS Additional fresh water tank Fresh water tank (heated and anti-freeze)(##) Waste water recovery tank with external vent Floor Fresh water recovery tank with external vent Waste water recovery tank with external vent 110 1. | Fuel tank | 60 l. | 120 l. |
| Maximum power kW (HP) 85 (115) (180) Mechanics(*)(**) Fiat Ducato 35 Fiat Ducato 43 Version Euro 5+ Wider rear track • DIMENSIONS AND WEIGHTS External length External width Internal height Internal width Maximum total weight Overall height Payload (about) Towable mass Towable mass | Gearbox | 5+1 | 011 |
| Version Euro 5+ Wider rear track ● DIMENSIONS AND WEIGHTS External length External width 2,300 mm Internal height 2,100 mm Internal width 217 cm Maximum total weight 3.650 - 4.250 - 4.400 Kg(PTM) (@@) Overall height 2,920 mm Payload (about) 696 Kg 846 - 1.406 - 1.556 Kg(PTM) Towable mass 1,600 Kg 2,000 Kg (130 150 180 HP) (PTM) Type-approved seats(@) 4 5 Weight in running order(#) 2,804 Kg 2,804-2,844-2,844 Kg(PTM) Wheelbase 3.800 mm THICKNESS Floor 55 mm 80 fm Roof 40 mm 40 mm Walls 35 mm 35 mm TANKS Additional fresh water tank 80 l. Fresh water tank (heated and anti-freeze)(##) 80 + 20 l. Waste water recovery tank with external vent 110 l. | Maximum power kW (HP) | 85 (115) | |
| Wider rear track ● DIMENSIONS AND WEIGHTS 6.590 mm External length 2,300 mm Internal height 2,100 mm Internal width 217 cm Maximum total weight 3.500 Kg 3.650 - 4.250 - 4.400Kg(PTM) (@@) Overall height 2,920 mm (@@) Payload (about) 696 Kg 846 - 1.406 - 1.556 Kg(PTM) Towable mass 1,600 Kg 2,000 Kg (130 150 180 HP) (PTM) Type-approved seats(@) 4 5 Weight in running order(#) 2,804 Kg 2,804-2,844-2,844 Kg(PTM) Wheelbase 3.800 mm THICKNESS Floor 55 mm Roof 40 mm Walls 35 mm TANKS Additional fresh water tank 80 l. Fresh water tank (heated and anti-freeze)(##) 80 + 20 l. Waste water recovery tank with external vent 110 l. | Mechanics(^)(^^) | Fiat Ducato 35 | Fiat Ducato 43 |
| DIMENSIONS AND WEIGHTS | Version | Euro 5+ | |
| External length | Wider rear track | • | |
| External width | DIMENSIONS AND WEIGHTS | | |
| Internal height | External length | 6.590 mm | |
| Internal width | External width | 2,300 mm | |
| Maximum total weight 3.500 Kg 3.650 - 4.250 - 4.400Kg(PTM) (@@) Overall height 2,920 mm Payload (about) 696 Kg 846 - 1.406 - 1.556 Kg(PTM) Towable mass 1,600 Kg 2,000 Kg (130 150 180 HP) (PTM) Type-approved seats(@) 4 5 Weight in running order(#) 2,804 Kg 2,804-2,844-2,844 Kg(PTM) Wheelbase 3.800 mm THICKNESS Floor 55 mm Roof 40 mm Walls 35 mm TANKS Additional fresh water tank 80 l. Fresh water tank (heated and anti-freeze)(##) 80 + 20 l. Waste water recovery tank with external vent 110 l. | Internal height | 2,100 mm | |
| 3.500 kg (@@) | Internal width | 217 cm | |
| Payload (about) 696 Kg 846 - 1.406 - 1.556 Kg(PTM) Towable mass 1,600 Kg 2,000 Kg (130 150 180 HP) Type-approved seats(@) 4 5 Weight in running order(#) 2,804 Kg 2,804-2,844-2,844 Kg(PTM Wheelbase 3.800 mm THICKNESS 55 mm Floor 55 mm Walls 35 mm TANKS 35 mm Additional fresh water tank 80 l. Fresh water tank (heated and anti-freeze)(##) 80 + 20 l. Waste water recovery tank with external vent 110 l. | Maximum total weight | 3.500 Kg | 3.650 - 4.250 - 4.400Kg(PTM) (@@) |
| Towable mass | Overall height | 2,920 mm | İ |
| Type-approved seats(@) | Payload (about) | 696 Kg | 846 - 1.406 - 1.556 Kg(PTM) |
| Weight in running order(#) 2,804 Kg 2,804-2,844-2,844 Kg(PTM Wheelbase 3.800 mm THICKNESS Floor 55 mm Roof 40 mm Walls 35 mm TANKS Additional fresh water tank 80 l. Fresh water tank (heated and anti-freeze)(##) 80 + 20 l. Waste water recovery tank with external vent 110 l. | Towable mass | 1,600 Kg | |
| Wheelbase 3.800 mm THICKNESS 55 mm Floor 55 mm Roof 40 mm Walls 35 mm TANKS Additional fresh water tank 80 l. Fresh water tank (heated and anti-freeze)(##) 80 + 20 l. Waste water recovery tank with external vent 110 l. | Type-approved seats(@) | 4 | 5 |
| THICKNESS Floor 55 mm Roof 40 mm Walls 35 mm TANKS Additional fresh water tank 80 l. Fresh water tank (heated and anti-freeze)(##) 80 + 20 l. Waste water recovery tank with external vent 110 l. | Weight in running order(#) | 2,804 Kg | 2,804-2,844-2,844 Kg(PTM) |
| 55 mm | Wheelbase | 3.800 mm | |
| Roof 40 mm Walls 35 mm TANKS 80 l. Additional fresh water tank 80 l. Fresh water tank (heated and anti-freeze)(##) 80 + 20 l. Waste water recovery tank with external vent 110 l. | THICKNESS | | |
| Walls 35 mm TANKS Additional fresh water tank 80 l. Fresh water tank (heated and anti-freeze)(##) 80 + 20 l. Waste water recovery tank with external vent 110 l. | Floor | 55 mm | |
| TANKS Additional fresh water tank 80 l. Fresh water tank (heated and anti-freeze)(##) 80 + 20 l. Waste water recovery tank with external vent 110 l. | Roof | 40 mm | |
| Additional fresh water tank 80 l. Fresh water tank (heated and anti-freeze)(##) 80 + 20 l. Waste water recovery tank with external vent 110 l. | Walls | 35 mm | |
| Fresh water tank (heated and anti-freeze)(##) 80 + 20 l. Waste water recovery tank with external vent 110 l. | TANKS | | |
| Waste water recovery tank with external vent 110 l. | Additional fresh water tank | | 80 l. |
| | Fresh water tank (heated and anti-freeze)(##) | 80 + 20 l. | |
| WC (antifreeze) with Thetford cassette 18 l. | Waste water recovery tank with external vent | 110 l. | |
| | WC (antifreeze) with Thetford cassette | 18 l. | 1 |

| ECOVIP 310 | STANDARD | OPTION | | STANDARD | OPTION |
|---|-----------------|----------------|--|------------------|----------------|
| EQUIPMENT | | | | | |
| Additional 12 V socket in the cab (max 180 W) | • | I | 360° swivelling table with telescopic leg | • | |
| Antitheft system, electrical, volumetric and perimetric | | • | Artificial leather upholstery | i | Firenze |
| Car radio antenna integrated in rear view mirror | • | 1 | Fine, real leather upholstery | i | Vip-Club |
| Central locking system in cab and living area | • | | Indirect lighting over the hanging cabinets | • | i |
| Electric step, can be operated from the dashboard with light | | | TV stand in the living area (hidden TV) | • | i |
| and acoustic warning sign | | | | <u> </u> | Bologna Como |
| Entrance door: double-locking, fixed window, blind, flyscreen and waste bin | • | | Upholstery with anti-stain treatment Verona To | | Torino |
| Front fog lights | İ | • | KITCHEN & WASHROOM | | |
| Headlamp leveller | • | İ | 230 V socket in the kitchen | | I |
| LED daytime running lights | İ | • | 3-burner hob | • | 1 |
| LED daytime running lights, integrated in the headlamps | • | İ | Additional work top, folding | 1 | 1 • |
| LED outdoor light | • | | Cloth-rack integrated in the shower ceiling | • | 1 |
| Midi Seitz roof-light in the living room(°°) | • | İ | Gas oven | 1 | <u> </u> |
| Motorcycle rack | İ | • | Seitz Mini-Heki roof-light in the kitchen | <u> </u> | 1 |
| Power windows | • | İ | Three-way fridge with mirrored smoke-effect finish and | 1 | 1 |
| Rear-view mirrors: heated, el. adjustable, wide angle tilt | • | İ | automatic energy source selection (AES) and external | 106 l. | |
| Seitz S4 windows with blinds and flyscreens | 4 | 1 + 1(***)(*) | inspection hatch | | |
| Single key for both doors and hatches | • | | Transparent roof-light in bathroom | 280 x 280 mm | <u> </u> |
| Stabilizer bar, front and rear | • | İ | Turbovent roof-light in the bathroom | 200 X 200 IIIIII | <u> </u> |
| Swivelling, upholstered cab seats with headrests, two armrests | | İ | Turbovent roof-light in the kitchen | <u> </u> | 1 • |
| and adjustable height and incline | • | | Wooden platform for shower plate | • | 1 |
| Two speakers in cab | • | Ì | Wooden place of the Shower place | | |
| Windscreen and side windows pleated blind (Remis), 3 pieces | • | | TECHNICAL EQUIPMENT | | |
| DEDC | | | 12 V sockets ~ 230 V sockets | 3 - 2 | |
| BEDS | | | Additional heater | 1 | • |
| Adjustable reading lights on all beds | • | | Battery charger 20A, automatic | • | |
| Berths | 4(°) | 2 | Heating system | Truma Combi 6 | İ |
| Dinette bed | 200x140 76 cm | | TV sockets in living room - rear bedroom | 1 - 1 | i |
| Electric drop-down bed above the dinette(°°) | | 191x130 125 cm | | ' | |
| Height under drop-down bed | 195 cm | | GARAGE | | |
| Rear bed with wooden slats | 215x150 136 cm | | ABS tank, washable, drain and stop | I • | 1 |
| Rear mattress in Biolatex | • | | Dimensions (W x H x L) | 217x128x95 cm | <u> </u> |
| | | | Garage load capacity | 220 Kg | 1 |
| FITTING-OUT | | | Left hatch (W x H) | 74x118 cm | 1 |
| Furniture design(&) | 1 | Noce Melinga | Loading motocycle on both sides | /+X110 CIII | 1 |
| | Rovere Trentino | Olmo Toscano | Right hatch (W x H) | 74x118 cm | 1 |
| Wardrobe with dual access (from front and top) | • | | Warning lamp on dashboard for open garage door | 7-1X110 CIII | 1 |
| Wardrobes | 1 1 | | realising lamp on dustious for open garage door | 1 | 1 |
| | 1 | 1 | | | |